

Quadro-Sicura® E 1

for building with basements

PRESSING WATER

- Single-compartment house lead-in **with sealing on both sides**
- Use in **on-site casing** or **waterproof concrete core bore** (white tank)
- Building services: gas, water, electricity and telecommunications
- With **additional seal flange** for use in accordance with DIN 18533 W2.1-E (black tank)



25 years guarantee



PRODUCT ADVANTAGES

- Infinitely variable modular gaskets for water or energy
- Leak-tight against gas and pressing water
- Extremely easy installation
- Light component weight
- Easy assignment of building service sealing through symbol identification

TECHNICAL DETAILS

- DVGW-approved
- Methane gas resistant
- Dry installation
- Relining possible when connecting jacket pipes
- Connection option for rigid or flexible jacket pipes DN 75. Larger or smaller diameters are possible via expansion sleeves or reductions
- The building service is given a dummy plug that is leak-tight against gas and pressing water
- With seal flange in accordance with DIN 18533

Supply lines	Pipe/cable Ø
Gas or	Gas house lead-ins RMA, Schuck, VAF Voigt, Burger: DN 25
Water or	Outer diameter 32 mm, 40 mm, 50 mm; optional outer diameter 63 mm
Electricity or	Outer diameter of 26–36 mm; optional outer diameter 36–47 mm
Telecommunications or	Outer diameter: 2 × 5–7 mm, 3 × 7–13 mm, 1 × 14–18 mm and 1 × 19–22 mm
For X-fibre optic cables (electricity, water, telecommunications, fibre optic cables)	Outer diameter: 2 × 5–7 mm, 2 × 7–13 mm, 1 × 12–16 mm, 1 × 23–40 mm

Building	Dimensions
Core bore/casing Ø	99–103 mm
Wall thicknesses	130–550 mm

Further dimensions and versions available upon request.

Sealing of building service	Article number
For RMA gas house lead-in	2811 000 000 00
For Schuck gas house lead-in	2812 000 000 00
For water	2810 000 010 00
For electricity, water, telecommunications, fibre optic cables (X-LWL)	2810 000 025 00

Prices do not include fixtures and pipes.



Variant: Quadro-Sicura® E1/wide for twin/element walls (160–550 mm)
Fig.: Quadro-Sicura® E1/wide for gas