

# Quadro-Sicura® E 2

for building with basements

PRESSING WATER

- Single-compartment house lead-in **with sealing on both sides**
- Use in **on-site casing** or **waterproof concrete core bore** (white tank)
- For the following building services: **gas, water, electricity and telecommunications**



## PRODUCT ADVANTAGES

- Infinitely variable modular gaskets for water or energy
- Leak-tight against gas and pressing water
- Extremely easy installation
- Light component weight
- Easy assignment of building service sealing through symbol identification

## TECHNICAL DETAILS

- DVGW-approved
- Methane gas resistant
- Optional installation in accordance with DIN 18195/ DIN 18533 possible
- Dry installation
- Relining possible when connecting jacket pipes
- Connection option for rigid or flexible jacket pipes DN 75. Larger or smaller diameters are possible via expansion sleeves or reductions
- The building service is given a dummy plug that is leak-tight against gas and pressing water

| Supply lines  | Pipe/cable Ø   |
|---|--|
| Gas or  | Gas house lead-ins RMA, Schuck, VAF Voigt, Burger: DN 25 (other dimensions available upon request) |
| Water or  | Outer diameter 32 mm, 40 mm, 50 mm; optional outer diameter 63 mm                                  |
| Electricity or  | Outer diameter of 26–36 mm; optional outer diameter 36–47 mm                                       |
| Telecommunications or   | Outer diameter: 2 × 5–7 mm, 3 × 7–13 mm, 1 × 14–18 mm and 1 × 19–22 mm                             |
| For X-fibre optic cables (electricity, water, telecommunications, fibre optic cables) | Outer diameter: 2 × 5–7 mm, 2 × 7–13 mm, 1 × 12–16 mm, 1 × 23–40 mm                                |

| Building           | Dimensions |
|--------------------|------------|
| Core bore/casing Ø | 99–103 mm  |
| Wall thicknesses   | 130–550 mm |

Further dimensions available upon request.

| Sealing of building service  | Article number  |
|--|-----------------|
| For RMA gas house lead-in  | 2821 000 000 00 |
| For Schuck gas house lead-in   | 2822 000 000 00 |
| For water  | 2820 000 010 00 |
| For electricity, water, telecommunications, fibre optic cables (X-LWL) | 2820 000 025 00 |

Prices do not include fixtures and pipes.



Variant: Quadro-Sicura® E2/wide for twin/element walls (180–550 mm)  
Fig.: Quadro-Sicura® E2/wide for X-LWL