

# Quadro-Sicura® MIS 40

for building with basements



- Single-compartment house lead-in with **injection system**
- Use in **the most common wall types** with sealing in accordance with **DIN 18533 W2.1-E** (black tank) or for **waterproof core bore** (white tank)
- For **fibre optic cables/pipes** or telecommunication lines



25  
years  
guarantee

## PRODUCT ADVANTAGES

- Ideal for sealing existing bitumen thick coatings
- Tensioning and sealing via resin injection using an integrated membrane system
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations

## TECHNICAL DETAILS

- Gas and water-tight up to 1 bar
- For open design
- Integrated plug sealing
- Without additional shrinking
- For bores in the most common wall types in accordance with DIN 18533 W2.1-E or for waterproof core bore (white tank)

## ▪ THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® MIS 40
- Wall termination sleeve
- Grid bow
- Expansion resin
- Quick-clamping device

Supply lines	Line diameters
Fibre optic cable/pipes	2 × 5–7 mm or 1 × 9–12 mm

Building	Dimensions
Core bore/casing Ø	40–50 mm
Wall thicknesses	200–900 mm, optionally 900–1,200 mm

Product	Line diameter	Article number
Quadro-Sicura® MIS 40 PU (packaging unit) 10 items	For 2 × (5–7 mm)	2100 006 000 00
	For 1 × (9–12 mm)	2100 012 000 00

Including 10 items from the 2 K resin system, one quick-clamping device and 10 grid bows.



## ACCESSORIES – ABSOLUTELY NECESSARY!

- 2K cartridge gun PP6

