

Quadro-Sicura® MIS 40S

for buildings without basements



- Single-compartment house lead-in with **injection system**
- Use as **angular penetration in floor slabs** made of **waterproof concrete**
- For **fibre optic cables/pipes** or telecommunication lines



25
years
guarantee

PRODUCT ADVANTAGES

- Suitable for retrofitting fibre optic cable/pipes or telecommunication lines
- Sealing via resin injection using an integrated membrane system
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Installation as angular penetration in floor slabs
- Gas and water-tight up to 1 bar
- For open design
- Integrated plug sealing
- Without additional shrinking
- Suitable for bores in floor slabs made of waterproof concrete, load class 1

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® MIS 40S
- Wall termination sleeve
- Grid bow
- Expansion resin
- Quick-clamping device

Supply lines	Line diameter
Fibre optic cable/pipes	2 × 5–7 mm or 1 × 9–12 mm

Building	Dimensions
Core bore/casing Ø	40–50 mm
Wall thicknesses	200–900 mm, optionally 900–1,200 mm

Product	Line diameter	Article number
Quadro-Sicura® MIS 40S PU (packaging unit) 10 items	2 × 5–7 mm	2100 006 000 30
	1 × 9–12 mm	2100 012 000 30

Including 10 items from the 2 K resin system, one quick-clamping device and 10 grid bows.

Article arriving in 2nd quarter of 2020



ACCESSORIES – ABSOLUTELY NECESSARY!

- 2K cartridge gun PP6

