


Quadro-Sicura® MIS 60 D

for building with basements



- Single-compartment house lead-in with **injection system**
- Use in **the most common wall types** with sealing in accordance with **DIN 18533 W2.1-E** (black tank) or for **waterproof core bore** (white tank)
- For **fibre optic cables/pipes** or **water lines**



25
years
guarantee

PRODUCT ADVANTAGES

- Ideal for sealing existing bitumen thick coatings
- Tensioning and sealing via resin injection using an integrated membrane system
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Gas and water-tight up to 1 bar
- For open design
- Integrated plug sealing
- Without additional shrinking
- For bores in the most common wall types in accordance with DIN 18533 W2.1-E or for waterproof core bore (white tank)

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® MIS 60 D
- Wall termination sleeve
- Grid bow (only for cables with Ø 5–12 mm)
- Expansion resin
- Quick-clamping device
- Base for lines with diameter 30–34 mm
- For deviating line diameter with selectable interchangeable insert

Supply lines	Line diameters
Fibre option/electric cables	30–34 mm or 24–30 mm or 18–24 mm or 12–18 mm or 6–12 mm or 4 × 5 mm – 7 mm or 3 × 10 mm (Please specify the diameter with your order)

Building	Dimensions
Core bore/casing Ø	62–65 mm
Wall thicknesses	200–900 mm optionally 900–1,200 mm

Other dimensions available upon request.

Product	Line diameter	Article number
Quadro-Sicura® MIS 60 D PU (packaging unit) 10 items	For 30–34 mm	2110 032 000 00
	For 24–30 mm	2110 025 000 00
	For 18–24 mm	2110 020 000 00
	For 12–18 mm	2110 015 000 00
	For 6–12 mm	2110 012 000 00
	For 4 × 5–7 mm	2110 007 000 00
	For 3 × 10 mm	2110 010 000 00

Including 10 items from the 2 K resin system, one quick-clamping device.



ACCESSORIES – ABSOLUTELY NECESSARY!

- 2K cartridge gun PP6

