


Quadro-Sicura® MIS 90

for building with basements

 PRESSING WATER

- Single-compartment house lead-in with **injection system**
- Use in **the most common wall types** with sealing in accordance with **DIN 18533 W2.1-E** (black tank) or for **waterproof core bore** (white tank)
- For **all cable types** or **water lines**



25
years
guarantee

PRODUCT ADVANTAGES

- Allows for the simultaneous routing of electricity or water and telecommunications
- Ideal for sealing existing bitumen thick coatings
- Tensioning and sealing via resin injection using an integrated membrane system
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Gas and water-tight up to 1 bar
- For open design
- For the most common pipe and cable diameters
- Integrated plug sealing
- Without additional shrinking
- For bores in the most common wall types in accordance with DIN 18533 W2.1-E or for waterproof core bore (white tank)

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® MIS 90
- Wall termination sleeve
- Expansion resin
- Quick-clamping device
- Selectable collar plugs

Supply lines	Line diameters
Water, electricity or telecommunications	1 × 24–40 mm or 3 × 7–12 mm or
	1 × 24–52 mm or
	1 × 14–21 mm or
	3 × 7–13 mm or
	1 × 5–13 mm
	(Please specify the diameter with your order)

Building	Dimensions
Core bore/casing Ø	92–102 mm
Wall thicknesses	200–900 mm optionally 900–1,200 mm

Further dimensions and versions available upon request.

Product	Line diameter	Article number
Quadro-Sicura® MIS 90 PU (packaging unit) 6 items	For 1 × (24–40 mm) or 3 × (7–12 mm)	2120 040 000 00
	For 1 × (24–52 mm)	2120 050 000 00
	For 1 × (14–21 mm), 3 × (7–13 mm) and 1 × (5–13 mm)	2120 020 000 00

Including 6 items from the 2 K resin system, one quick-clamping device.



ACCESSORIES – ABSOLUTELY NECESSARY!

- 2K cartridge gun PP6

