

Quadro-Sicura® MIS 90S

for buildings without basements

 PRESSING WATER

- Single-compartment house lead-in with injection system
- Use as angular penetration in floor slabs made of waterproof concrete
- For all cable types or water lines



25
years
guarantee

PRODUCT ADVANTAGES

- Allows for the simultaneous routing of electricity or water and telecommunications
- Sealing via resin injection using an integrated membrane system
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Installation as angular penetration in floor slabs
- Gas and water-tight up to 1 bar
- For open design
- For the most common pipe and cable diameters
- Integrated plug sealing
- Without additional shrinking
- Suitable for bores in floor slabs made of waterproof concrete, load class 1

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® MIS 90S
- Wall termination sleeve
- Expansion resin
- Quick-clamping device
- Selectable collar plugs

Supply lines	Line diameter
Water, electricity or telecommunications	1 × 24–40 mm or 3 × 7–12 mm or
	1 × 24–52 mm or
	1 × 14–21 mm or
	3 × 7–13 mm or
	1 × 5–13 mm
	(Please specify the diameter with your order)

Building	Dimensions
Core bore/casing Ø	92–102 mm
Wall thicknesses	200–1,200 mm

Further dimensions and versions available upon request.

Product	Line diameter	Article number
Quadro-Sicura® MIS 90S PU (packaging unit) 6 items	1 × 24–40 mm and 3 × 7–12 mm	2120 040 000 30
	1 × 24–52 mm	2120 050 000 30
	1 × 14–21 mm, 3 × 7–13 mm and 1 × 5–13 mm	2120 020 000 30

Including 6 items from the 2 K resin system, one quick-clamping device.

Article arriving in 2nd quarter of 2020



ACCESSORIES – ABSOLUTELY NECESSARY!

- 2K cartridge gun PP6

