

Quadro-Sicura® Nova 1-FW

for building with basements

PRESSING WATER

- Multi-compartment house lead-in **with sealing on both sides**
- Use in **on-site casing** or **waterproof concrete core bore** (white tank)
- With **additional seal flange** for use in accordance with DIN 18533 W2.1-E (black tank)
- For the following building services: district/geothermal heating, water, electricity and telecommunications



25
years
guarantee

PRODUCT ADVANTAGES

- Infinitely variable modular gaskets for water and energy
- Leak-tight against gas and pressing water
- Extremely easy installation
- Space-saving building lead-in of supply lines
- Easy assignment of building service sealing through symbol identification
- Installation without torque spanner possible

TECHNICAL DETAILS

- Dry installation
- Installation in core bores or casings with an inner diameter of 298–304 mm
- District heating supply and return in one or two jacket pipes
- Sealing of the district/geothermal pipes, water pipes, electricity and telecommunication cables is independent from the individual building services
- Variable arrangement of individual compartments possible
- Infinitely adjustable for wall thicknesses of 200–550 mm
- No additional outer seal required
- Connection option for rigid or flexible jacket pipes DN 75 and DN 125; larger or smaller dimensions are possible via expansion sleeves or reductions
- Visual indication of the tightening torque via control pins
- With seal flange in accordance with DIN 18533

Supply lines	Pipe/cable Ø
Local/district heating	Outer diameter 75 mm, 90 mm, 110 mm; optionally 125 mm
or	
Geothermal heating	Outer diameter 32 mm, 40 mm, 50 mm Please specify the diameter with your order
Water	Outer diameter 32 mm, 40 mm, 50 mm; optional outer diameter 63 mm
Electricity	Outer diameter of 26–36 mm; optional outer diameter 36–47 mm
Telecommunications	Outer diameter: 2 × 5–7 mm, 3 × 7–13 mm, 1 × 14–18 mm and 1 × 19–22 mm

Building	Dimensions
Core bore/casing Ø	298–304 mm
Wall thicknesses	200–550 mm

Further dimensions and versions available upon request.

Optional diameters	Article number
2 × 75, 90 or 110 mm	2310 075 000 00
2 × 32–50 mm	Please specify the diameter with your order

Prices do not include fixtures and pipes.



Variant: Quadro-Sicura® Nova
1-FW/wide for twin/element walls