



# Quadro-Sicura® Quick/G

for building with basements

 PRESSING WATER

- Single-compartment house lead-in with **injection system**
- Use in **the most common wall types** with sealing in accordance with **DIN 18533 W2.1-E** or for **waterproof core bore (white tank)**
- For the building service **gas**
- With seal flange in accordance with **DIN 18533 (black tank)**
- Ideal for **new connections** in existing buildings



## PRODUCT ADVANTAGES

- With Easy Fix System for easy, fast and safe installation
- With ITL system for optimal contact pressure
- Installation without additional tensioning device
- Allows for the simultaneous routing of gas house lead-in combinations and fibre optic cables/pipes (2 × Ø 7 mm)
- Ideal for sealing existing bitumen thick coatings
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations
- No additional mechanical fastening required

## TECHNICAL DETAILS

- DVGW-approved (RMA and Schuck)
- Gas and water-tight up to 1 bar
- For open design
- Suitable for RMA/Schuck/VAF Voigt/Burger gas house lead-ins
- For bores in the most common wall types with sealing in accordance with DIN 18533 W2.1-E or for waterproof core bore (white tank)

## THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® Quick/G
- Wall termination sleeve
- Expansion resin



### ACCESSORIES – ABSOLUTELY NECESSARY!

- 2K cartridge gun PP6

Supply lines	Gas house lead-in type
Gas	RMA, Schuck, VAF Voigt or Burger

Building	Dimensions
Core bore/casing Ø	99–103 mm
Wall thicknesses	200 – max. 1,140 mm (depending on gas house lead-in type)

Product	Article number
RMA DN 25	2611 025 000 10
Schuck DN 25	2612 025 000 10
VAF-Voigt DN 25	2613 025 000 10
Burger DN 25 + DN 32	2614 025 000 10

Prices do not include fixtures and pipes.