


Quadro-Sicura® Quick/O

for building with basements

 PRESSING WATER

- Single-compartment house lead-in with **injection system**
- Use in **the most common wall types** with sealing in accordance with **DIN 18533 W2.1-E** or for **waterproof core bore** (white tank)
- For sealing **sewer pipes DN 110**
- With seal flange in accordance with **DIN 18533** (black tank)
- Ideal for **new connections** in existing buildings



PRODUCT ADVANTAGES

- With Easy Fix System for easy, fast and safe installation
- With ITL system for optimal contact pressure
- Installation without additional tensioning device
- Ideal for sealing existing bitumen thick coatings
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Gas and water-tight up to 1 bar
- For open design
- For bores in the most common wall types with sealing in accordance with DIN 18533 W2.1-E or for waterproof core bore (white tank)

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® Quick/O
- Wall termination ring
- Expansion resin

Sewer pipe	Pipe Ø
Nominal/outer diameter 110	Outer diameter: 110 mm

Building	Dimensions
Core bore/casing Ø	149–153 mm
Minimum wall thickness	200 mm

Product	Article number
Quadro-Sicura® Quick/O	2620 110 000 10

Delivery/price without sewer pipe.



ACCESSORIES – ABSOLUTELY NECESSARY!

- 2K cartridge gun PP6