


# Quadro-Sicura® Quick/X

for building with basements

 PRESSING WATER

- Single-compartment house lead-in with **injection system**
- Use in **the most common wall types** with sealing in accordance with **DIN 18533 W2.1-E** or for **waterproof core bore (white tank)**
- For **all cable types** or **water lines**
- With seal flange in accordance with **DIN 18533** (black tank)
- Ideal for **new connections** in existing buildings



For water or electricity



For telecommunications



For X-fibre optic cables



## PRODUCT ADVANTAGES

- With Easy Fix System for easy, fast and safe installation
- With ITL system for optimal contact pressure
- Installation without additional tensioning device
- Ideal for sealing existing bitumen thick coatings
- Connection of jacket pipes possible
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations

## TECHNICAL DETAILS

- Gas and water-tight up to 1 bar
- For open design
- For the most common pipe and cable diameters
- Integrated plug sealing
- Without additional shrinking
- For bores in the most common wall types with sealing in accordance with DIN 18533 W2.1-E or for waterproof core bore (white tank)
- Relining possible when connecting jacket pipes
- Connection option for rigid or flexible jacket pipes DN 75. Larger or smaller diameters possible.

## THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® Quick/X
- Wall termination ring
- Expansion resin
- Jacket pipe end plugs



### ACCESSORIES – ABSOLUTELY NECESSARY!

- 2K cartridge gun PP6

Supply lines	Pipe/cable Ø
<b>Water or energy</b>	Outer diameter: 26–63 mm
<b>X-fibre optic cables</b>	Outer diameter: 2 × 5–7 mm, 2 × 7–13 mm, 1 × 12–16 mm and 1 × 23–40 mm
<b>Telecommunications</b>	Outer diameter: 2 × 5–7 mm, 3 × 7–13 mm, 1 × 14–18 mm and 1 × 19–22 mm

Building	Dimensions
<b>Core bore/casing Ø</b>	99–103 mm
<b>Wall thicknesses</b>	200–550 mm, optionally up to 1,200 mm

Further dimensions and versions available upon request.

Product	Article number
Water or energy	2600 000 910 10
Telecom	2600 000 912 10
X-fibre optic cables	2600 000 925 10

Prices do not include fixtures and pipes.

## Ring plug (building interior)

For sealing the circular gap between the pipe and the casing

Product	Article number
Ring plug for water or energy	2990 703 916 50
Ring plug for telecommunications	2990 703 913 50
Ring plug for X-fibre optic cables	2990 703 914 50

