


Quadro-Sicura® SD

for buildings without basements

 NICHTDRÜCKENDES WASSER

- Single-compartment house lead-in with **injection system**
- Use as angular penetration in floor slabs made of **concrete**
- For **cable types** or **water lines**



25
years
guarantee

PRODUCT ADVANTAGES

- Suitable for retrofitting for electricity or water through floor slabs
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Installation as angular penetration in floor slabs
- Gas and water-tight
- For open design
- For the most common pipe and cable diameters
- Integrated plug sealing
- Without additional shrinking
- Suitable for bores in floor slabs made of concrete of load class 2 in accordance with the Waterproofing guideline

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® SD
- Expansion resin

Supply lines	Line diameter [mm]
Water or electricity	26–50

Building	Dimensions
Core bore/casing Ø	99–104 mm
Wall thicknesses	200–1,200 mm

Further dimensions and versions available upon request.

Product	Dimensions	Article number
Quadro-Sicura® SD PU (packaging unit) 1 item*	26–50 mm (further dimensions possible)	2140 000 001 00
Quadro-Sicura® SD PU (packaging unit) 10 items**	26–50 mm (further dimensions possible)	2140 000 010 00

* including one 2 K resin system
** including ten 2 K resin system



ACCESSORIES – ABSOLUTELY NECESSARY!

- 2K cartridge gun PP6

