

INSTALLATION DETAILS

HKD floor drain

- HKD floor drain
- HKD Floor drain with foil flange



HKD floor drain



HKD Floor drain with foil flange

Assembly

- Apply a suitable lubricant to the insertion end of the floor drain and insert it into the existing duct. Upper edge of drain housing = floor slab upper edge. Check vertical alignment of the drain housing.
- Place the provided construction time protective cover at the top of the floor drain.
- After concreting check whether stacking frame and may be stacking frame extension can be adjusted to correct height when installed.
- Stacking frame top edge = top edge of final floor cover
- If necessary, cut the extension to the appropriate length.
- Insert the gasket ring into the top of the drain housing.
- Apply lubricant to the stacking frame and may be the stacking extension and insert it into the drain housing.
- Adjust the stacking frame to the required height and alignment.
- After laying the screed/final floor cover, insert the sludge basket and grating.

Installation details for HKD floor drain with foil flange

- Install the floor drain in the formwork in such a way that the upper edge of the floor slab will later be level with the foil flange. To do this, shorten the floor element at the pointed end and chamfer again.
- Glue the EPDM foil flange with a suitable adhesive to the floor slab, e.g. APP-PU 50.
- When applying a sealing membrane, protect the floor element from excessive heat generation.

Accessories (optional)

- stainless steel grid
- stainless steel grid, screwed
- extension piece
- extension of stacking frame
- APP-PU 50 (polyurethane adhesive)

DOYMA products are continuously being further developed. Technical changes will be performed without prior notice.

Further info at www.doyma.de

DOYMA GmbH & Co

SEALING SYSTEMS
FIRE PROTECTION SYSTEMS

Industriestr. 43-57
28876 Oyten

Phone: 0 42 07/91 66-300
Fax: 0 42 07/91 66-199

www.doyma.de
info@doyma.de