


Quadro-Sicura® MIS 60S

for buildings without basements



- Single-compartment house lead-in with injection system
- Use as angular penetration in floor slabs made of waterproof concrete
- For fibre optic cables/pipes or water lines



PRODUCT ADVANTAGES

- Suitable for retrofitting fibre optic cable/pipes or water lines
- Sealing via resin injection using an integrated membrane system
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Installation as angular penetration in floor slabs
- Leak-tight against gas and pressing water up to 1 bar
- radon proof – according to FHRK information sheet MB101
- For open design
- Integrated plug sealing
- Without additional shrinking
- Suitable for bores in floor slabs made of waterproof concrete, load class 1

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Sicura® MIS 60S
- Wall termination sleeve
- Expansion resin
- Quick-clamping device
- Base for line diameter 30–34 mm
- For deviating line diameter with selectable interchangeable insert



ACCESSORIES

Grid bow (for max. line diameter of 16 mm only)

ACCESSORIES – RECOMMENDED

- 2K cartridge gun

Supply lines	Line diameter
Fibre optic/electric cables	30–34 mm or 24–30 mm or 18–24 mm or 12–18 mm or 6–12 mm or 4 × 5–7 mm or 3 × 10 mm (Please specify the diameter with your order)

Dimensions	
Core bore/pipe sleeve Ø	62–65 mm
Design length	1,300 mm

Other dimensions available upon request.

Product	Line diameter	Article number
Quadro-Sicura® MIS 60S PU (packaging unit) 10 items	for 30 – 34 mm	2110 032 000 30
	for 24 – 30 mm	2110 025 000 30
	for 18 – 24 mm	2110 020 000 30
	for 12 – 18 mm	2110 015 000 30
	for 6 – 12 mm	2110 012 000 30
	for 4 x 5 – 7 mm	2110 007 000 30
	for 3 x 10 mm	2110 010 000 30

Including 10 items from the 2K resin system, one quick-clamping device.