NEW

DOYMAfix® Connect HP/P Pro

PRESSING WATER

- Connection system for floor slabs
- Installation in unfinished structures made of waterproof concrete
- For air-water heat pumps (monoblock)
- Complete package for installation and commissioning
- Stainless steel corrugated pipe for high flexibility during installation

25 Jahre Garantie

PRODUCT BENEFITS

- Complete package contains all required assemblies and components for connection and sealing
- Ready to connect immediately; all common adapter nipples included
- Stainless steel corrugated pipe offers high flexibility for connection (yields without pushing back)
- Flexible creation of bends without fittings
- Quick and easy installation without special tools
- One-person installation
- All media lines protected by flexible jacket pipe DN200
- Separate routing of pipes and cables
- Power and control cables routed separately
- Required cables (mains/control lines) can be pulled through quickly and easily
- Low bending radius of 0.5 m
- Certified gas-tightness
- 100% oxygen-tight stainless steel corrugated pipes
- Self-cleaning effect thanks to corrugation
- Cross-disciplinary assembly (shell, electrical, HVAC) creates flexibility in the construction process

TECHNICAL DETAILS

- Gas and water-tight
- Radon-proof according to FHRK leaflet MB 101
-

THE BUILDING PENETRATION SYSTEM CONSISTS OF

- Flexible jacket pipe DN200
- Stainless steel corrugated pipes DN32 or DN40 including insulation
- Cable protection pipes DN32
- Terminators DN200
- Connection sets for DN32 or DN40
- Sealing systems HKD wall collar DN200
- Bend fixture
- Building connection section warning strap

Subject to technical changes. Some illustrations include accessories.

F-MT-1-804-01/2026

DOYMAfix® Connect HP/P Pro

Connecting line	Pipe/cable diameters
Stainless steel corrugated pipes	AD 41 mm, ID 33 mm (DN32) or AD 48 mm, ID 40 mm (DN40)
Cable protection pipe	AD 32 mm, ID 25 mm
Cables	2 x 9-12 mm and 2 x 12-17 mm
Adapter nipples	G1 1/4" AG (DN32) G1 1/2" AG (DN40)

Dimensions	
Center distance of the stainless steel corrugated pipes	90 mm

Product	DN	Length	Article number
DOYMAfix® Connect HP/P Pro (DOYMAfix® Connect HP Pro + HKD wall collar)	32	5 m	5 25 0 032 200 0 5
	40	10 m	5 25 0 040 200 1 0
	40	15 m	5 25 0 040 200 1 5
	40	20 m	5 25 0 040 200 2 0

Subject to technical changes. Some illustrations include accessories.