# UGA BKD 150
# system cap

**With sockets and heat shrink sleeves**

PRESSING WATER

- Use in existing flange sleeves and on-wall flange sealing collars
- Sealing of media lines using shrink technology
- With bayonet closure

## PRODUCT ADVANTAGES

- Gas and watertight
- For routing media lines (cables or pipes) measuring 7–108 mm
- Sealing with heat or cold-shrink technology
- Compatible with other established systems
- Made of environmentally friendly and chemically highly resistant materials

### System cap closed

| Article | Number of cables | Article number |
|---|---|---|
| BKD150-D | 0 | 4 10 1 000 150 0 4 |

### System cap with heat shrink sleeve

| Article | Cables | Outer diameter of pipe/cable | Article number |
|---|---|---|---|
| BKD150-D-1/80-TM | 1 | 26–78 mm | 4 10 1 080 150 04 |
| BKD150-D-1/110-TM | 1 | 34–108 mm | 4 10 1 110 150 04 |
| BKD150-D-3/59(3/3)-TM | 3 | 22–57 mm | 4 10 1 059 150 04 |
| BKD150-D-7/38(7/6)-TM* | 7 | 7–37 mm | 4 10 1 038 150 04 |
| BKD150-D-8/35(4/2)/25(4/2)-TM** | 8 | 4 × 7–24 mm / 4 × 7–34 mm | 4 10 1 035 150 04 |

### System cap with cold shrink sleeve

| Article | Number of cables | Outer diameter of pipe/cable |
|---|---|---|
| BKD150-D-1/80-KS | 1 | 33–79 mm |
| BKD150-D-1/110-KS | 1 | 38–109 mm |
| BKD150-D-3/59(3/3)-KS | 3 | 21–57 mm |
| BKD150-D-7/38(7/6)-KS* | 7 | 20–37 mm |
| BKD150-D-8/35(4/2)/25(4/2)-KS** | 8 | 4 × 11–24 mm / 4 × 16–34 mm |

* BKD150-D-7 includes one closed socket in the scope of delivery. which can be opened up as needed. The scope of delivery includes six shrink sleeves.

** BKD150-D-8 includes four closed sockets in the scope of delivery (two each of 35 and 25 mm). which can be opened up as needed. The scope of delivery includes four shrink sleeves; further shrink sleeves are available as accessories in sets of four.

The UGA range is excluded from the DOYMA 25-year warranty.

Subject to technical changes. Some illustrations include accessories.