# Curaflam® Inject BS+K10

- For flammable and fire-proof pipes and individual cables
- Building services: wastewater, drinking water, gas, heating, cooling, compressed air, sprinkler, electrical

R 90
P-3138/0325
abP

Baustoffzulassung
ETA-21/0909
ETA

25 Jahre Garantie

## FOR PENETRATION SEALING PIPES AND CABLES ACCORDING TO (M)LAR:

- Steel, stainless steel, copper, cast iron Ø ≤ 160 mm
- Aluminium Ø ≤ 32 mm
- Plastic, plastic composite Ø ≤ 32 mm
- Individual cables and optical fibre

## FOR PENETRATION SEALING IN COMPLIANCE WITH P-3138/0325-MPA BS, OF PIPES MADE OF:

- Steel, stainless steel (wall/ceiling) Ø ≤ 88.9 mm / ≤ 60.3 mm
- Copper, cast iron (wall/ceiling) Ø ≤ 54.0 mm / ≤ 42.0 mm
- Including synthetic rubber insulation (for exact type see general building inspection certificate), insulation thickness ≤ 56.0 mm

## INSTALLATION CONDITIONS

- In ceilings with a thickness (M)LAR or P-3138/0325-MPA BS ≥ 80 mm / 150 mm
- In walls with a thickness (M)LAR or P-3138/0325-MPA BS ≥ 80 mm / 150 mm

The requirements of the MLAR applicable in each case must be observed, especially the distance stipulations.

Detailed information concerning the application areas and provisions for execution please refer to the Verification & Applicability documents.

O-MT-2-907-01/2026

Subject to technical changes. Some illustrations include accessories.

## Curaflam® Inject BS+K10

**Penetration sealing of fire-proof/flammable supply/disposal pipes**

In accordance with (M)LAR

| Ø [mm] | Annular space [mm] | Depth [mm] | Required cartridges |
|---|---|---|---|
| 32 | 15 | 150 | Approx. 1 |
| 63 | | | Approx. 2 |
| 110 | | | Approx. 3 |
| 160 | | | Approx. 4 |

| Ø [mm] | Annular space [mm] | Depth [mm] | Required cartridges |
|---|---|---|---|
| 32 | 50 | 5 | Approx. 1 |
| 63 | | | |
| 110 | | | |
| 160 | | | |

* Plug the middle of the circular gap in advance with mineral wool at least 80 mm deep (fire-proof, melting point ≥ 1000°C)

| Content | Article number |
|---|---|
| 300 ml | 3 25 0 000 000 0 0 |

Scope of delivery: cartridge 300 ml including fire protection shield, installation instructions.

## Curaflam® Inject BS+K10 installed

Subject to technical changes. Some illustrations include accessories.