Quadro-Secura® ADS

for buildings without basements

PRESSING WATER

- Single-compartment house lead-in as a round version
- Use in unfinished structures made of waterproof concrete
- For utilities gas or water
- House lead-ins with larger dimensions

Quadro-Secura® ADS gas

Quadro-Secura® ADS water

PRODUCT ADVANTAGES

- Bend-resistant jacket pipes for compliance with bending radii
- Subsequent replacement of pipes and cables possible (relining)

TECHNICAL DETAILS

- Leak-tight against gas and pressing water
- radon proof – according to FHRK information sheet MB 101
- Suitable for immediate installation in the floor slab or for later retrofitting in a cut-out in the floor slab
- One installation part, consisting of Schuck house lead-ins combination including tear-off protection and anti-twist protection, as well as pre-assembled gasket inserts
- Cast-in part consisting of plastic pipe sleeve and one connecting sleeve including integrated bend-resistant jacket pipe and height-adjustable rod

Type/version	House lead-in combination [DN]	Plastic pipe sleeve [DN]	Inner diameter Jacket pipe [mm]
Quadro-Secura® ADS gas/water	50	100	110
Quadro-Secura® ADS gas/water	80	150	150

Further dimensions and versions available upon request.

DN of house lead-in combination
50
80

Equipped with 3 m bend-resistant jacket pipe.

The Quadro-Secura ADS system is excluded from the DOYMA 25-year warranty.

Subject to technical changes. Some illustrations include accessories.

T-MT-1-514-01/2026