# Quadro-Secura® building owner's package
# Split heat pump FOR BUILDINGS **WITHOUT BASEMENTS**

## The solution for refrigerant lines for split heat pumps!

### APPLICATION

House-lead-ins for refrigerant lines
Use in unfinished floor slabs to be made of waterproof concrete (white tank)

### PRODUCT ADVANTAGES

- Bend-resistant jacket pipe (inner diameter 110 mm/length 10 m) for compliance with bending radii
- Pipes and cables can be laid independently from construction progress
- Leak-tight against gas and pressing water
- Gasket insert is to be retrofitted around existing refrigerant lines
- With quick release for safe and secure closure

Subject to technical changes. Some illustrations include accessories.
T-MT-1-514-01/2026

## COMPONENTS/SCOPE OF DELIVERY

**1x Quadro-Secura® ADS DN 100**

Cast-in part for embedding in the floor slab, including bend-resistant jacket pipe (inner diameter 110 mm/length 10 m)

25 years guarantee

**1x Curaflex Nova® Uno/M/Z**

Gasket insert with replaceable onion ring inserts
DN 100 for refrigerant lines and cables
Including fixing tabs for easy installation

25 years guarantee

### ACCESSORIES – OPTIONAL

- ITL nut set

| Quadro-Secura® building owner's package. split heat pump for buildings without basements | Outer diameter of cable [mm] | Outer diameter of pipe [inches] | Article number |
|---|---|---|---|
| Incl. 10 m bend-resistant jacket pipe | 2 x 6-15 | 1/4 + 1/2 | ***2040 100 028 91*** |
| Incl. 10 m bend-resistant jacket pipe | 2 x 6-15 | 3/8 + 5/8 | ***2040 100 027 91*** |
| Incl. 10 m bend-resistant jacket pipe | 2 x 6-15 | 1/4 + 5/8 | ***2040 100 029 91*** |

Prices do not include fixtures and pipes/cables.

| inch | Outer diameter |
|---|---|
| 1/4 | 6,4 mm |
| 1/2 | 12,7 mm |
| 3/8 | 9,5 mm |
| 5/8 | 15,9 mm |



Subject to technical changes. Some illustrations include accessories.