Quadro-Secura® MIS 40D

for buildings with basements

PRESSING WATER

- Single-compartment house lead-in with injection system
- Use in the most common wall types with sealing in accordance with DIN 18533 W2.1-E (black tank) or for core bore in waterproof concrete (white tank)
- For fibre optic cables/pipes or telecommunication lines

25 years guarantee

PRODUCT ADVANTAGES

- Ideal for sealing existing bitumen thick coatings
- Tensioning and sealing via resin injection using an integrated membrane system
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Leak-tight against gas and pressing water up to 1 bar
- radon proof – according to FHRK information sheet MB101
- For open design
- Integrated plug sealing
- Without additional shrinking
- For bores in the most common wall types in accordance with DIN 18533 W2.1-E or for core bore in waterproof concrete (white tank)

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Secura® MIS 40D
- Wall termination sleeve
- Grid bow
- Expansion resin
- Quick-clamping device

Supply lines	Line diameters
Fibre optic cable/pipes	5 – 12 mm, divided into individual ranges (see table below)

Dimensions	
Core bore/pipe sleeve Ø	40–50 mm
Wall thicknesses	200–900 mm, optionally 900–1200 mm

Product	Line diameter	Article number
Quadro-Secura® MIS 40D PU (packaging unit) 10 items	1 x 9 - 12 mm	2100 012 000 00
	2 x 5 - 7 mm	2100 006 000 00

Including 10 items from the 2K resin system. one quick-clamping device and 10 grid bows.

ACCESSORIES – RECOMMENDED

- 2K cartridge gun

Subject to technical changes. Some illustrations include accessories.

U-MT-1-514-09/2026