Quadro-Secura® Quick/H

for buildings with basements

PRESSING WATER

- Single-compartment house lead-in with injection system
- Use in the most common wall types with sealing in accordance with DIN 18533 W2.1-E (black tank) or for core bore in waterproof concrete (white tank)
- No additional pipe sleeve required
- For holding the Curaflex Nova® sealing systems
- With seal flange in accordance with DIN 18533 (black tank)
- Ideal for new connections in existing buildings

ITL RADON TIGHT IAF GmbH 25 years guarantee

PRODUCT ADVANTAGES

- With Easy Fix System for easy, fast and safe installation
- With ITL system for optimal contact pressure
- Installation without additional tensioning device
- Ideal for sealing existing bitumen thick coatings
- Can even be used with conventional hollow bricks without filling
- Quick installation
- Suitable for building renovations

TECHNICAL DETAILS

- Leak-tight against gas and pressing water up to 1 bar
- radon-tight – according to FHRK information sheet MB101 meets the requirements for radon precautionary areas
- for an open construction
- Integrated casing suitable for the Curaflex Nova® andCuraflex Nova® sealing systems
- Can be sealed to smaller pipe diameters using an adapters-leeve (accessory for type DN 160 and DN 200)
- For bores in the most common wall types with sealing in accordance with DIN 18533 W2.1-E (black tank) and for core bores in waterproof concrete (white tank)
- Casing offers connection option for rigid or flexible jacket pipes
- Relining possible when connecting jacket pipes

THE HOUSE LEAD-IN CONSISTS OF:

- Quadro-Secura® Quick/H
- Wall termination ring
- Expansion resin

Product	Type	Article number
Quadro-Secura® Quick/H	110	2630 110 760 1 0
Quadro-Secura® Quick/H	160	2630 160 760 1 0
Quadro-Secura® Quick/H	200	2630 200 760 1 0

Preis ohne Curaflex® Dichtungssystem und Leitung.

Dimensions

Type DN/OD [mm]	Inner-Ø Sleeve Tube [mm]	Core bore/pipe sleeve diameter [mm]	Outer-Ø seal flange [mm]	Dimensions Wall Thicknesses [mm]	Suitable for Sealing System
110	100	149 – 153	250	200 – 600 (optional bis 1200)	Curaflex® und Curaflex Nova®
160	150	199 – 203	300		
200	190	249 – 253	350	200 – 550	Curaflex® Sonder

Accessories Optional

Adapter sleeve [DN]	Sealing on	Article number
160/125	110 – 125 mm	2990 160 125 0 0
160/140	130 – 145 mm	2990 160 140 0 0
200/175	160 – 180 mm	2990 200 175 0 0

ACCESSORIES – RECOMMENDED

- Curaflex® / Curaflex Nova® sealing systems
- 2K cartridge gun

Example: Adapter Sleeve

Subject to technical changes. Some illustrations include accessories. U-MT-1-514-08/2026